



The Power to Surprise

## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SDS # : 089195

### KIA ORIGINAL OIL 0W-30 C2

Date of the previous version: not applicable

Revision Date: 2018-12-19

Version 1

#### Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

##### 1.1. Product identifier

Product name	KIA ORIGINAL OIL 0W-30 C2
Number	TGM
Substance/mixture	Mixture

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Motor oil.
-----------------	------------

##### 1.3. Details of the supplier of the safety data sheet

Supplier	TOTAL LUBRIFIANTS 562 Avenue du Parc de L'île 92029 Nanterre Cedex FRANCE Tél: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71
----------	--

##### For further information, please contact:

Contact Point	HSE
E-mail Address	rm.msds-lubs@total.com

##### 1.4. Emergency telephone number

Emergency telephone: +44 1235 239670  
France - ORFILA (INRS) Tél : +33 (0)1 45 42 59 59  
In France - Poison centers:  
ANGERS : 02 41 48 21 21  
BORDEAUX : 05 56 96 40 80  
LILLE : 08 00 59 59 59  
LYON : 04 72 11 69 11  
MARSEILLE : 04 91 75 25 25  
NANCY : 03 83 22 50 50  
PARIS : 01 40 05 48 48  
STRASBOURG : 03 88 37 37 37  
TOULOUSE : 05 61 77 74 47

#### Section 2: HAZARDS IDENTIFICATION

##### 2.1. Classification of the substance or mixture

REGULATION (EC) No 1272/2008



The Power to Surprise

SDS # : 089195

**KIA ORIGINAL OIL 0W-30 C2**

Revision Date: 2018-12-19

Version 1

*For the full text of the H-Statements mentioned in this Section, see Section 2.2.***Classification**

The product is not classified as dangerous according to Regulation (EC) No. 1272/2008

2.2. Label elements**Labelled according to**

REGULATION (EC) No 1272/2008

**Signal word**

None

**Hazard Statements**

None

**Precautionary Statements**

None

**Supplemental Hazard Statements**

EUH210 - Safety data sheet available on request

EUH208 - Contains C14-16-18 Alkyl phenol. May produce an allergic reaction

2.3. Other hazards**Physical-Chemical Properties**

Contaminated surfaces will be extremely slippery.

**Environmental properties**The product may form an oil film on the water surface that may stop the oxygen exchange.  
Should not be released into the environment.**Section 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixture**Hazardous ingredients**

Chemical Name	EC-No	REACH registration No	CAS-No	Weight %	Classification (Reg. 1272/2008)
Distillates (petroleum), hydrotreated heavy paraffinic	265-157-1	01-2119484627-25	64742-54-7	40-<50	Asp. Tox. 1 (H304)
bis(nonylphenyl)amine	253-249-4	01-2119488911-28	36878-20-3	1-<2.5	Aquatic Chronic 4 (H413)
C14-16-18 Alkyl phenol	931-468-2	01-2119498288-19	^	1-<2.5	STOT RE 2 (H373) Skin Sens. 1B (H317)

**Additional information**

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346.

**For the full text of the H-Statements mentioned in this Section, see Section 16.****Section 4: FIRST AID MEASURES**



The Power to Surprise

SDS # : 089195

**KIA ORIGINAL OIL 0W-30 C2**

Revision Date: 2018-12-19

Version 1

4.1. Description of first-aid measures

<b>General advice</b>	IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before reuse.
<b>Inhalation</b>	Remove casualty to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration.
<b>Ingestion</b>	Clean mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.
<b>Protection of First-aiders</b>	First aider needs to protect himself. See Section 8 for more detail. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

4.2. Most important symptoms and effects, both acute and delayed

<b>Eye contact</b>	Not classified based on available data.
<b>Skin contact</b>	Not classified based on available data. May produce an allergic reaction.
<b>Inhalation</b>	Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system.
<b>Ingestion</b>	Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes to physician</b>	Treat symptomatically.
---------------------------	------------------------

Section 5: FIRE-FIGHTING MEASURES
-----------------------------------

5.1. Extinguishing media

<b>Suitable Extinguishing Media</b>	Carbon dioxide (CO <sub>2</sub> ). ABC powder. Foam. Water spray or fog.
<b>Unsuitable Extinguishing Media</b>	Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

<b>Special Hazard</b>	Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may
-----------------------	--



The Power to Surprise

SDS # : 089195

**KIA ORIGINAL OIL 0W-30 C2**

Revision Date: 2018-12-19

Version 1

be highly dangerous if inhaled in confined spaces or at high concentration. Combustion products include sulphur oxides ( SO<sub>2</sub> and SO<sub>3</sub> ) and Hydrogen sulphide H<sub>2</sub>S, Mercaptans, Nitrogen oxides (NO<sub>x</sub>), Phosphorous oxides, Zinc oxides.

5.3. Advice for fire-fighters

**Special protective equipment for fire-fighters** Wear self-contained breathing apparatus and protective suit.

**Other information** Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

**Section 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures

**General Information** Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

6.2. Environmental precautions

**General Information** Do not allow material to contaminate ground water system. Prevent entry into waterways, sewers, basements or confined areas. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

**Methods for containment** Dike to collect large liquid spills. If necessary dike the product with dry earth, sand or similar non-combustible materials.

**Methods for cleaning up** Dispose of contents/container in accordance with local regulation. In case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations.

6.4. Reference to other sections

**Personal Protective Equipment** See Section 8 for more detail.

**Waste treatment** See section 13.

**Section 7: HANDLING AND STORAGE**7.1. Precautions for safe handling

**Advice on safe handling** For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.

**Prevention of fire and explosion** Take precautionary measures against static discharges.

**Hygiene measures** Ensure the application of strict rules of hygiene by the personnel exposed to the risk of



The Power to Surprise

SDS # : 089195

**KIA ORIGINAL OIL 0W-30 C2**

Revision Date: 2018-12-19

Version 1

contact with the product. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Regular cleaning of equipment, work area and clothing is recommended. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

7.2. Conditions for safe storage, including any incompatibilities**Technical measures/Storage conditions**

Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Store at room temperature. Protect from moisture.

**Materials to Avoid**

Strong oxidizing agents.

7.3. Specific end uses**Specific use(s)**

Please refer to Technical Data Sheet for further information.

**Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters**Exposure limits**

Mineral oil mist:  
USA: OSHA (PEL) TWA 5 mg/m<sup>3</sup>, NIOSH (REL) TWA 5 mg/m<sup>3</sup>, STEL 10 mg/m<sup>3</sup>, ACGIH (TLV) TWA 5 mg/m<sup>3</sup> (highly refined)

**Legend**

See section 16

**Derived No Effect Level (DNEL)****DNEL Worker (Industrial/Professional)**

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7				5.4 mg/m <sup>3</sup> /8h (aerosol - inhalation)
bis(nonylphenyl)amine 36878-20-3			0.62 mg/kg bw/day Dermal 4.37 mg/m <sup>3</sup> Inhalation	
C14-16-18 Alkyl phenol ^			1.17 mg/m <sup>3</sup> (inhalation) 0.30 mg/kg bw/day (dermal)	

**DNEL Consumer**

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Distillates (petroleum),				1.2 mg/m <sup>3</sup> /24h (aerosol -



The Power to Surprise

SDS # : 089195

**KIA ORIGINAL OIL 0W-30 C2**

Revision Date: 2018-12-19

Version 1

hydrotreated heavy paraffinic 64742-54-7				inhalation)
bis(nonylphenyl)amine 36878-20-3			2.5 mg/kg bw/day (Dermal) 0.25 mg/kg bw/day (Oral)	

**Predicted No Effect Concentration (PNEC)**

Chemical Name	Water	Sediment	Soil	Air	STP	Oral
bis(nonylphenyl)amine 36878-20-3	0.1 mg/l fw 0.01 mg/l mw 1 mg/l or	132000 mg/kg dw fw 13200 mg/kg dw mw	263000 mg/kg dw		1 mg/l	
C14-16-18 Alkyl phenol ^	0.100 mg/l (fw) 0.010 mg/l (mw) 1 mg/ (or)	4266.16 mg/kg sediment dw (fw) 426.62 mg/kg sediment dw (mw)	852.58 mg/kg soil dw		100 mg/l	

8.2. Exposure controls**Occupational Exposure Controls****Engineering Measures**

Apply technical measures to comply with the occupational exposure limits. Ensure adequate ventilation, especially in confined areas. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.

**Personal Protective Equipment****General Information**

Protective engineering solutions should be implemented and in use before personal protective equipment is considered. The personal protective equipment (PPE) recommendations apply to the product ITSELF. In case of mixtures or formulations, it is suggested that you contact the relevant PPE suppliers.

**Respiratory protection**

None under normal use conditions. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387). Type A/P1. Warning ! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.

**Eye Protection**

If splashes are likely to occur, wear: Safety glasses with side-shields. EN 166.

**Skin and body protection**

Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing. Type 4/6.

**Hand Protection**

Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. In case of prolonged contact with the product, it is recommended to wear gloves complying with EN 420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the



The Power to Surprise

SDS # : 089195

**KIA ORIGINAL OIL 0W-30 C2**

Revision Date: 2018-12-19

Version 1

gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

**Environmental exposure controls****General Information**

The product should not be allowed to enter drains, water courses or the soil.

**Section 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties

<b>Appearance</b>		limpid	
<b>Color</b>		yellow	
<b>Physical State @20°C</b>		liquid	
<b>Odor</b>		Characteristic	
<b>Odor Threshold</b>		No information available	
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	<b>Method</b>
<b>pH</b>		Not applicable	
<b>Melting point/range</b>		Not applicable	
<b>Boiling point/boiling range</b>		No information available	
<b>Flash point</b>	<b>200 °C</b> <b>392 °F</b>		ASTM D92 ASTM D92
<b>Evaporation rate</b>		No information available	
<b>Flammability Limits in Air</b>			
<b>upper</b>		No information available	
<b>Lower</b>		No information available	
<b>Vapor Pressure</b>		No information available	
<b>Vapor density</b>		No information available	
<b>Relative density</b>	0.840 - 0.860	@ 15 °C	
<b>Density</b>	840 - 860 kg/m <sup>3</sup>	@ 15 °C	
<b>Water solubility</b>		Insoluble	
<b>Solubility in other solvents</b>		No information available	
<b>logPow</b>		No information available	
<b>Autoignition temperature</b>		No information available	
<b>Decomposition temperature</b>		No information available	
<b>Viscosity, kinematic</b>	43.6 mm <sup>2</sup> /s	@ 40 °C	ISO 3104
<b>Explosive properties</b>	Not explosive		
<b>Oxidizing Properties</b>	Not applicable		
<b>Possibility of hazardous reactions</b>	None under normal processing		

9.2. Other information

**Freezing Point** No information available

**Section 10: STABILITY AND REACTIVITY**



The Power to Surprise

SDS # : 089195

**KIA ORIGINAL OIL 0W-30 C2**

Revision Date: 2018-12-19

Version 1

10.1. Reactivity**General Information** None under normal processing.10.2. Chemical stability**Stability** Stable under recommended storage conditions.10.3. Possibility of hazardous reactions**Hazardous Reactions** No dangerous reaction known under conditions of normal use.10.4. Conditions to avoid**Conditions to avoid** Keep away from open flames, hot surfaces and sources of ignition. Keep away from heat and sparks.10.5. Incompatible materials**Materials to Avoid** Strong oxidizing agents.10.6. Hazardous Decomposition Products**Hazardous Decomposition Products** Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Combustion products include sulphur oxides ( SO<sub>2</sub> and SO<sub>3</sub> ) and Hydrogen sulphide H<sub>2</sub>S, Mercaptans, Nitrogen oxides (NO<sub>x</sub>), Phosphorous oxides, Zinc oxides.

Section 11: TOXICOLOGICAL INFORMATION
---------------------------------------

11.1. Information on toxicological effects**Acute toxicity Local effects Product Information****Skin contact** . Not classified based on available data. May produce an allergic reaction.**Eye contact** . Not classified based on available data.**Inhalation** . Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system.**Ingestion** . Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.**Acute toxicity - Component Information**

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated heavy	LD50 > 5000 mg/kg bw (rat -	LD50 > 5000 mg/kg bw (rabbit -	LC50 (4h) > 5 mg/l (aerosol) (rat -





The Power to Surprise

SDS # : 089195

**KIA ORIGINAL OIL 0W-30 C2**

Revision Date: 2018-12-19

Version 1

paraffinic	OECD 420)	OECD 402)	OECD 403)
bis(nonylphenyl)amine	LD50 > 5000 mg/kg (Rat - OECD 401)	LD50 > 2000 mg/kg (Rat - OECD 402)	
C14-16-18 Alkyl phenol	LD50 2000 mg/kg bw (rat)	LD50 2000 mg/kg bw (rat)	

**Sensitization****Sensitization**

Not classified based on available data. The supplier of one or more of the components contained within this formulation has indicated that he has data on the components and/or similar mixtures, which confirms that at the concentration used, classification is not required. Contains sensitizer(s). May produce an allergic reaction.

**Specific effects****Carcinogenicity**

Not classified based on available data. During use in engines, contamination of oil with low levels of combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.

**Mutagenicity****Germ Cell Mutagenicity**

Not classified based on available data.

**Reproductive toxicity**

Not classified based on available data.

**Repeated dose toxicity****Target Organ Effects (STOT)****Specific target organ systemic toxicity (single exposure)**

Not classified based on available data.

**Specific target organ systemic toxicity (repeated exposure)**

Not classified based on available data.

**Aspiration toxicity**

Not classified based on available data.

**Other information****Other adverse effects**

Characteristic skin lesions (pimples) may develop following prolonged and repeated exposures (contact with contaminated clothing).

**Section 12: ECOLOGICAL INFORMATION****12.1. Toxicity**

Not classified based on available data.

**Acute aquatic toxicity - Product Information**

No information available.

**Acute aquatic toxicity - Component Information**



The Power to Surprise

SDS # : 089195

**KIA ORIGINAL OIL 0W-30 C2**

Revision Date: 2018-12-19

Version 1

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7	EL50 (48h) > 100 mg/l (Pseudokirchnerella subcapitata - OECD 201)	EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202)	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	
bis(nonylphenyl)amine 36878-20-3	EC50(72h) 600 mg/l (Selenastrum capricornutum)	EC50 (48h) > 100 mg/l (Daphnia magna - OECD 202)	LC50(96h) > 100 mg/l (Zebra Fish)	EC50(0.1 d) > 1,000 mg/l (Sludge)
C14-16-18 Alkyl phenol ^		EC50(48h) > 100 mg/l (Daphnia magna - static - OECD202)		

**Chronic aquatic toxicity - Product Information**

No information available.

**Chronic aquatic toxicity - Component Information**

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7		NOEL (21d) 10 mg/l (Daphnia magna - QSAR Petrotox)	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	

**Effects on terrestrial organisms**

No information available.

12.2. Persistence and degradability**General Information**

No information available.

12.3. Bioaccumulative potential**Product Information**

No information available.

**logPow**

No information available

**Component Information**

Chemical Name	log Pow
Distillates (petroleum), hydrotreated heavy paraffinic - 64742-54-7	-
bis(nonylphenyl)amine - 36878-20-3	7.7

12.4. Mobility in soil**Soil**

Given its physical and chemical characteristics, the product generally shows low soil mobility.

**Air**

Loss by evaporation is limited.

**Water**

The product is insoluble and floats on water.



The Power to Surprise

SDS # : 089195

**KIA ORIGINAL OIL 0W-30 C2**

Revision Date: 2018-12-19

Version 1

12.5. Results of PBT and vPvB assessment**PBT and vPvB assessment** No information available.12.6. Other adverse effects**General Information** No information available.**Section 13: DISPOSAL CONSIDERATIONS**13.1. Waste treatment methods

**Waste from Residues / Unused Products** Should not be released into the environment. Dispose of in accordance with the European Directives on waste and hazardous waste. Where possible recycling is preferred to disposal or incineration. After use, this oil must be sent to a licensed waste oil facility. Incorrect disposal of used oil poses a risk to the environment. Mixture with other waste types such as solvents, brake- and cooling liquids is forbidden.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

**EWC Waste Disposal No.** According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used. The following Waste Codes are only suggestions: 13 02 06. 13 02 05.

**Other information** Refer to section 8 for safety and protective measures for disposal personnel.

**Section 14: TRANSPORT INFORMATION**ADR/RID Not regulatedIMDG/IMO Not regulatedICAO/IATA Not regulatedADN Not regulated**Section 15: REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

**REACH**



The Power to Surprise

SDS # : 089195

## KIA ORIGINAL OIL 0W-30 C2

Revision Date: 2018-12-19

Version 1

All substances contained in this mixture have been pre-registered, registered or are exempt from registration in accordance with Regulation (CE) No. 1907/2006 (REACH)

### International Inventories

All the substances contained in this product are listed or exempted from listing in the following inventories:

U.S.A. (TSCA)  
Korea (KECL)  
Philippines (PICCS)  
Canada (DSL/NDL)  
Australia (AICS)  
Europe (EINECS/ELINCS/NLP)

### Further information

No information available

### 15.2. Chemical Safety Assessment

**Chemical Safety Assessment** No information available

### Section 16: OTHER INFORMATION

#### Full text of H-Statements referred to under sections 2 and 3

H304 - May be fatal if swallowed and enters airways

H317 - May cause an allergic skin reaction

H373 - May cause damage to organs through prolonged or repeated exposure

H413 - May cause long lasting harmful effects to aquatic life

#### Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals

LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

DNEL = Derived No Effect Level

PNEC = Predicted No Effect Concentration

dw = dry weight

fw = fresh water



The Power to Surprise

SDS # : 089195

**KIA ORIGINAL OIL 0W-30 C2**

Revision Date: 2018-12-19

Version 1

mw = marine water  
or = occasional release

**Legend** Section 8

TWA: Time Weight Average  
STEL: Short Time Exposure Limit  
PEL: Permissible exposure limit  
REL: Recommended exposure limit  
TLV: Threshold Limit Values

+	Sensitizer	*	Skin designation
**	Hazard Designation	C:	Carcinogen
M:	Mutagen	R:	Toxic to reproduction

Revision Date: 2018-12-19  
Revision Note \*\*\* Indicates updated section.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006**

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

**End of the Safety Data Sheet**