

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SDS #: 089193 KIA ORIGINAL OIL 5W-30 A5/B5

Date of the previous version: not	applicable	Revision Date: 2018-12-18	Version 1
Section 1: IDENTIFICATIO COMPANY/UNDERTAKING		STANCE/MIXTURE AND OF THE	
1.1. Product identifier			
Product name Number Substance/mixture	KIA ORIGINAL C TGK Mixture	DIL 5W-30 A5/B5	
1.2. Relevant identified u	ses of the subs	tance or mixture and uses advised against	
Identified uses	Motor oil.		
1.3. Details of the supplie	er of the safety	data sheet	
Supplier	TOTAL LUBRIFIA 562 Avenue du P 92029 Nanterre C FRANCE Tél: +33 (0)1 41 3 Fax: +33 (0)1 41	arc de L'ile Cedex 35 40 00	

For further information, please contact:

Contact Point	HSE
E-mail Address	rm.msds-lubs@total.com

1.4. Emergency telephone number

Emergency telephone: +44 1235 239670 France - ORFILA (INRS) Tél : +33 (0)1 45 42 59 59 In France - Poison centers: ANGERS : 02 41 48 21 21 BORDEAUX : 05 56 96 40 80 LILLE : 08 00 59 59 59 LYON : 04 72 11 69 11 MARSEILLE : 04 91 75 25 25 NANCY : 03 83 22 50 50 PARIS : 01 40 05 48 48 STRASBOURG : 03 88 37 37 37 TOULOUSE : 05 61 77 74 47

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

REGULATION (EC) No 1272/2008



KIA ORIGINAL OIL 5W-30 A5/B5

Revision Date: 2018-12-18

Version 1

For the full text of the H-Statements mentioned in this Section, see Section 2.2.

Classification

The product is not classified as dangerous according to Regulation (EC) No. 1272/2008

2.2. Label elements

Labelled according to

REGULATION (EC) No 1272/2008

Signal word None

Hazard Statements None

Precautionary Statements None

Supplemental Hazard Statements EUH210 - Safety data sheet available on request

2.3. Other hazards

Physical-Chemical Properties	Contaminated surfaces will be extremely slippery.
Environmental properties	The product may form an oil film on the water surface that may stop the oxygen exchange.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixture

Chemical nature Hazardous ingredients

Mineral oil of petroleum origin.

Chemical Name	EC-No	REACH registration No	CAS-No	Weight %	Classification (Reg. 1272/2008)
Distillates (petroleum), hydrotreated heavy paraffinic	265-157-1	01-2119484627-25	64742-54-7	20-<30	Asp. Tox. 1 (H304)
Distillates (petroleum), solvent-dewaxed heavy paraffinic	265-169-7	01-2119471299-27	64742-65-0	5-<10	Asp. Tox. 1 (H304)
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	276-738-4	01-2119474889-13	72623-87-1	1-<3	Asp. Tox. 1 (H304)
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	276-737-9	01-2119474878-16	72623-86-0	1-<3	Asp. Tox. 1 (H304)
Tetrapropenyl phenol	310-154-3	01-2119513207-49	121158-58-5	0.01-<0.025	Skin Corr. 1C (H314) Eye Dam. 1 (H318) Repr. 1B (H360F)



Revision Date: 2018-12-18

Version 1

		Aquatic Acute 1 (H400)
		Aquatic Chronic 1 (H410)
		Acute M factor 10
		Chronic M factor 10

Additional information Product containing mineral oil with less than 3% DMSO extract as measured by IP 346.

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section 4: FIRST AID MEASURES

4.1. Description of first-aid measures

General advice	IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before reuse.
Inhalation	Remove casualty to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration.
Ingestion	Clean mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.
Protection of First-aiders	First aider needs to protect himself. See Section 8 for more detail. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

4.2. Most important symptoms and effects, both acute and delayed

Eye contact	Not classified based on available data.
Skin contact	Not classified based on available data.
Inhalation	Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician	Treat symptomatically.	
Section 5: FIRE-FIGH	TING MEASURES	

5.1. Extinguishing media



SDS #: 089193 KIA ORIGINAL OIL 5W-30 A5/B5			
	Revision Date: 2018-12-18	Version 1	
Suitable Extinguishing Media	Carbon dioxide (CO 2). ABC powder. Foam. Water spray or fog.		
Unsuitable Extinguishing Media	Do not use a solid water stream as it may scatter and spread fire.		
5.2. Special hazards arisir	ng from the substance or mixture		
Special Hazard	Incomplete combustion and thermolysis may produce gases of varying toxicity carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. be highly dangerous if inhaled in confined spaces or at high concentration. Corproducts include sulphur oxides (SO2 and SO3) and Hydrogen sulphide H2S Phosphorous oxides. Nitrogen oxides (NOx). Mercaptans. Zinc oxides.	These may ombustion	
5.3. Advice for fire-fighter	<u>S</u>		
Special protective equipment for fire-fighters	Wear self-contained breathing apparatus and protective suit.		

Other information Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

6.2. Environmental precautions

General Information Do not allow material to contaminate ground water system. Prevent entry into waterways, sewers, basements or confined areas. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Methods for containment	Dike to collect large liquid spills. If necessary dike the product with dry earth, sand or similar non-combustible materials.
Methods for cleaning up	Dispose of contents/container in accordance with local regulation. In case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations.

6.4. Reference to other sections

Personal Protective Equipment	See Section 8 for more detail.
Waste treatment	See section 13.

Section 7: HANDLING AND STORAGE



Revision Date: 2018-12-18

Version 1

7.1. Precautions for safe handling

Advice on safe handling	For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.
Prevention of fire and explosion	Take precautionary measures against static discharges.
Hygiene measures	Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Regular cleaning of equipment, work area and clothing is recommended. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions	Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Store at room temperature. Protect from moisture.				
Materials to Avoid	Strong oxidizing agents.				
7.3. Specific end uses					

Please refer to Technical Data Sheet for further information.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

 Exposure limits
 Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined)

Legend

Specific use(s)

See section 16

Derived No Effect Level (DNEL)

DNEL Worker (Industrial/Professional)

Chemical Name	· ·	Short term, local effects	• • •	Long term, local effects
	effects		effects	
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7				5.4 mg/m³/8h (aerosol - inhalation)



KIA ORIGINAL OIL 5W-30 A5/B5

Revision Date: 2018-12-18

Version 1

Distillates (petroleum),				5.4 mg/m ³ /8h (aerosol -
solvent-dewaxed heavy				inhalation)
paraffinic				
64742-65-0				
Lubricating oils				5.4 mg/m ³ /8h (aerosol -
(petroleum), C20-50,				inhalation)
hydrotreated neutral				
oil-based				
72623-87-1				F A and (2001) (1000) b
Lubricating oils				5.4 mg/m ³ /8h (aerosol -
(petroleum), C15-30,				inhalation)
hydrotreated neutral oil-based				
72623-86-0				
Tetrapropenyl phenol	166 mg/kg bw/day		0.25 mg/kg bw/day	
121158-58-5	Dermal		Dermal	
121100 00 0	44.18 mg/m ³ Inhalation		1.7621 mg/m ³ Inhalation	
ONEL Consumer			J	
Chemical Name	Short term, systemic	Short term, local effects	Long term, systemic	Long term, local effects
	effects	,	effects	. .
Distillates (petroleum),				1.2 mg/m ³ /24h (aerosol -
hydrotreated heavy				inhalation)
paraffinic				
64742-54-7				
Distillates (petroleum),				1.2 mg/m ³ /24h (aerosol -
solvent-dewaxed heavy				inhalation)
paraffinic				
64742-65-0				1.2 mg/m3/24b (20rosol
Lubricating oils				
Lubricating oils (petroleum), C20-50,				1.2 mg/m³/24h (aerosol - inhalation)
Lubricating oils (petroleum), C20-50, hydrotreated neutral				
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based				
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based 72623-87-1				inhalation)
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based 72623-87-1 Lubricating oils				inhalation)
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based 72623-87-1				inhalation) 1.2 mg/m³/24h (inhalation
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based 72623-87-1 Lubricating oils (petroleum), C15-30,				inhalation) 1.2 mg/m³/24h (inhalation
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based 72623-87-1 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0				inhalation) 1.2 mg/m³/24h (inhalation
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based 72623-87-1 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0 Tetrapropenyl phenol	50 mg/kg bw/day Dermal		0.075 mg/kg bw/day	inhalation) 1.2 mg/m³/24h (inhalation
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based 72623-87-1 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0	13.26 mg/m ³ Inhalation		Dermal	inhalation) 1.2 mg/m³/24h (inhalatior
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based 72623-87-1 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0 Tetrapropenyl phenol				1.2 mg/m ³ /24h (inhalatior -aerosol)

Predicted No Effect Concentration (PNEC)

Chemical Name	Water	Sediment	Soil	Air	STP	Oral
Lubricating oils						9.33 mg/kg food
(petroleum),						
C20-50,						
hydrotreated neutral						
oil-based						
72623-87-1						



KIA ORIGINAL OIL 5W-30 A5/B5

Revision Date: 2018-12-18

Version 1

-	Tetrapropenyl	0.000074 mg/l fw	0.226 mg/kg fw	0.118 mg/kg dw	100 mg/l	4 mg/kg food
	phenol	0.0000074 mg/l	dw		-	
	121158-58-5	mw	0.0266 mg/kg mw			
		0.00037 mg/l or	dw			

8.2. Exposure controls

Occupational Exposure Controls

Engineering Measures	Apply technical measures to comply with the occupational exposure limits. Ensure adequate ventilation, especially in confined areas. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.
Personal Protective Equipment	
General Information	Protective engineering solutions should be implemented and in use before personal protective equipment is considered. The personal protective equipment (PPE) recommendations apply to the product ITSELF. In case of mixtures or formulations, it is suggested that you contact the relevant PPE suppliers.
Respiratory protection	None under normal use conditions. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387). Type A/P1. Warning ! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.
Eye Protection	If splashes are likely to occur, wear:. Safety glasses with side-shields. EN 166.
Skin and body protection	Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing. Type 4/6.
Hand Protection	Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. In case of prolonged contact with the product, it is recommended to wear gloves complying with EN 420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Environmental exposure controls

General Information	The product should not be allowed to enter drains, water courses or the soil.
Section 9: PHYSICAL AND (CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance



KIA ORIGINAL OIL 5W-30 A5/B5

Revision Date: 2018-12-18

Version 1

Color Physical State @20°C Odor Odor Threshold		amber liquid Characteristic No information available	
<u>Property</u> pH Melting point/range	<u>Values</u>	Remarks Not applicable Not applicable	<u>Method</u>
Boiling point/boiling range		No information available	
Flash point Evaporation rate Flammability Limits in Air	200 °C 392 °F	No information available	ASTM D92 ASTM D92
upper Lower Vapor Pressure Vapor density Relative density Density Water solubility Solubility in other solvents logPow Autoignition temperature Decomposition temperature Viscosity, kinematic Explosive properties Oxidizing Properties Possibility of hazardous reactions	0.843 - 0.863 843 - 863 kg/m ³ 60.16 mm2/s Not explosive Not applicable None under normal proce	No information available No information available No information available On information available On 15 °C On 15 °C Insoluble No information available No information available No information available No information available On information available On information available On information available On information available On information available	ASTM D445

9.2. Other information

Freezing Point

No information available

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

General Information

None under normal processing.

10.2. Chemical stability

Stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous Reactions

No dangerous reaction known under conditions of normal use.



Revision Date: 2018-12-18

Version 1

10.4. Conditions to avoid

Conditions to avoid Keep away from open flames, hot surfaces and sources of ignition. Keep away from heat and sparks.

10.5. Incompatible materials

Materials to Avoid Strong oxidizing agents.

10.6. Hazardous Decomposition Products

Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Phosphorous oxides. Nitrogen oxides (NOx). Mercaptans. Combustion products include sulphur oxides (SO2 and SO3) and Hydrogen sulphide H2S. Zinc oxides.

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity Local effects Product Information

Skin contact	. Not classified based on available data.
Eye contact	. Not classified based on available data.
Inhalation	. Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	. Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
ATEmix (inhalation-dust/mist)	13.30 mg/l

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated heavy	LD50 > 5000 mg/kg bw (rat -	LD50 > 5000 mg/kg bw (rabbit -	LC50 (4h) > 5 mg/l (aerosol) (rat -
paraffinic	OECD 420)	OECD 402)	OECD 403)
Distillates (petroleum), solvent-dewaxed	LD50 > 5000 mg/kg bw (rat -	LD50 > 5000 mg/kg bw (rabbit -	LC50 (4h) > 5.53 mg/l (aerosol)
heavy paraffinic	OECD 420)	OECD 402)	(rat - OECD 403)
Lubricating oils (petroleum), C20-50,	LD50 > 5000 mg/kg bw (rat -	LD50 > 5000 mg/kg bw (rabbit -	LC50 (4h) > 5 mg/l (aerosol) (rat -
hydrotreated neutral oil-based	OECD 401)	OECD 402)	OECD 403)
Lubricating oils (petroleum), C15-30,	LD50 > 5000 mg/kg bw (Rat -	LD50 > 2000 mg/kg (Rabbit -	LD50 (4h) > 5.53 mg/l (Rat -
hydrotreated neutral oil-based	OECD TG 401)	OECD 402)	OECD 403)
Tetrapropenyl phenol	LD50 2100-2200 mg/kg (Rat)	LD50 15000 mg/kg (Rabbit)	

Sensitization

Sensitization

Not classified based on available data.

Specific effects



SDS # : 089193	KIA ORIGINAL OIL 5W-30 A5/B5	
	Revision Date: 2018-12-18	Version 1
Carcinogenicity	Not classified based on available data. During use in engines, contaminat levels of combustion products occurs. Used motor oils have been shown cancer in mice following repeated application and continuous exposure. E skin contact with used motor oil is not expected to have serious effects in is thoroughly removed by washing with soap and water.	to cause skin Brief or intermittent
Mutagenicity Germ Cell Mutagenicity	Not classified based on available data.	
Reproductive toxicity	Not classified based on available data. Contains toxic substance(s) listed reproduction.	as toxic to

Chemical Name	European Union
Tetrapropenyl phenol	Repr. 1B (H360F)
121158-58-5	

Repeated dose toxicity

Target Organ Effects (STOT)

Specific target organ systemic toxicity (single exposure)	Not classified based on available data.
Specific target organ systemic toxicity (repeated exposure)	Not classified based on available data.
Aspiration toxicity	Not classified based on available data.
Other information	
Other adverse effects	Characteristic skin lesions (pimples) may develop following prolonged and repeated exposures (contact with contaminated clothing).

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Not classified based on available data.

Acute aquatic toxicity - Product Information

No information available.

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7	EL50 (48h) > 100 mg/l (Pseudokirchnerella subcapitata - OECD 201)	EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202)	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	
Distillates (petroleum), solvent-dewaxed heavy paraffinic		EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202)	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	



KIA ORIGINAL OIL 5W-30 A5/B5

Revision Date: 2018-12-18

Version 1

0.17.10.05.0	_ · · · · · · · · · · · · · · · · · · ·			
64742-65-0				
Lubricating oils (petroleum),	EL50 (48h) > 100 mg	EL50 (48h) > 10000 mg/l	LL50 (96h) > 100 mg/l	
C20-50, hydrotreated neutral	(Pseudokirchnerella	(Daphnia magna - OECD	(Oncorhynchus mykiss -	
oil-based	subcapitata - OECD 201)	202)	OECD 203)	
72623-87-1		LL50 (24h) > 10000 mg/l	0202200)	
12020 01 1		(Gammarus pulex - OECD		
		202)		
		LL50 (48h) > 10000 mg/l		
		(Gammarus pulex - OECD		
		202)		
		LL50 (72h) > 10000 mg/l		
		(Gammarus pulex - OECD		
		202)		
		LL50 (96h) > 10000 mg/l		
		(Gammarus pulex - OECD		
		202)		
Lubricating oils (petroleum),		EL50(48h) >1000 mg/l	LL50 (96h) > 100 mg/l	
C15-30, hydrotreated neutral		(OECD TG 202)	(OECD TG 203)	
		(OECD 1G 202)	(OECD 1G 203)	
oil-based				
72623-86-0				
Tetrapropenyl phenol	EbC50 (72h) 0.15 mg/l	EC50(48h) 0.037 mg/l	EL50(96h) 40 mg/l	
121158-58-5	(Scenedesmus subspicatus -	(Daphnia magna - static -	Pimephales promelas	
	OECD 201)	OECD 202)	semi-static (OECD 203)	

Chronic aquatic toxicity - Product Information

No information available.

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7		NOEL (21d) 10 mg/l (Daphnia magna - QSAR Petrotox)	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	
Distillates (petroleum), solvent-dewaxed heavy paraffinic 64742-65-0		NOEL (21d) 10 mg/l (Daphnia magna - OECD 211)	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based 72623-87-1	NOEL (72h) >= 100 mg/l (Pseudokirchnerella subcapitata - OECD 201)	NOEL (21d) 10 mg/l (Daphnia magna - OECD 211)	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox) NOEL (96h) > 100 mg/l (Pimephales promelas - OECD 203)	
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0		NOEL (21d) = 10 mg/l (OECD TG 202)	NOELR (14d) > 1000 mg/l (QSAR modelled data)	
Tetrapropenyl phenol 121158-58-5		NOEC(21d) 0.0037 mg/l (Daphnia magna - semi-static - OECD 211)		

Effects on terrestrial organisms

No information available.



Version 1

SDS #: 089193

KIA ORIGINAL OIL 5W-30 A5/B5

Revision Date: 2018-12-18

12.2. Persistence and degradability

General Information No information available.

12.3. Bioaccumulative potential

Product Information

No information available.

logPow

No information available

Component Information

Chemical Name	log Pow
Distillates (petroleum), hydrotreated heavy paraffinic - 64742-54-7	-
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based - 72623-87-1	4.1
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based - 72623-86-0	6.1
Tetrapropenyl phenol - 121158-58-5	7.14

12.4. Mobility in soil

Soil	Given its physical and chemical characteristics, the product generally shows low soil mobility.	
Air	Loss by evaporation is limited.	
Water	The product is insoluble and floats on water.	
12.5. Results of PBT and vPvB assessment		
PBT and vPvB assessme	No information available.	

12.6. Other adverse effects

General Information

No information available.

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues / Unused Products	Should not be released into the environment. Do not empty into drains. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations. Where possible recycling is preferred to disposal or incineration.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.
EWC Waste Disposal No.	According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application



Revision Date: 2018-12-18

Version 1

for which the product was used. The following Waste Codes are only suggestions:. 13 02 05.

Other information

Refer to section 8 for safety and protective measures for disposal personnel.

Section 14: TRANSPORT INFORMATION

ADR/RID	Not regulated
IMDG/IMO	Not regulated
	Not regulated
ADN	Not regulated

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

REACH

All substances contained in this mixture have been pre-registered, registered or are exempt from registration in accordance with Regulation (CE) No. 1907/2006 (REACh)

International Inventories All the substances contained in this product are listed or exempted from listing in the following inventories: China (IECSC) Philippines (PICCS) U.S.A. (TSCA) Australia (AICS) Japan (ENCS) Canada (DSL/NDSL) Korea (KECL)

Further information

No information available

15.2. Chemical Safety Assessment

Chemical Safety Assessment No information available

Section 16: OTHER INFORMATION



Revision Note

KIA ORIGINAL OIL 5W-30 A5/B5

Revision Date: 2018-12-18

Version 1

Full text of H-Statements referred to under sections 2 and 3 H304 - May be fatal if swallowed and enters airways H314 - Causes severe skin burns and eye damage H318 - Causes serious eye damage H360F - May damage fertility H400 - Very toxic to aquatic life H410 - Very toxic to aquatic life with long lasting effects Abbreviations, acronyms ACGIH = American Conference of Governmental Industrial Hygienists bw = body weight bw/day = body weight/day EC x = Effect Concentration associated with x% response GLP = Good Laboratory Practice IARC = International Agency for Research of Cancer LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals LL = Lethal Loading NIOSH = National Institute of Occupational Safety and Health NOAEL = No Observed Adverse Effect Level NOEC = No Observed Effect Concentration NOEL = No Observed Effect Level OECD = Organization for Economic Co-operation and Development OSHA = Occupational Safety and Health Administration UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material DNEL = Derived No Effect Level PNEC = Predicted No Effect Concentration dw = dry weight fw = fresh water mw = marine water or = occasional release Legend Section 8 TWA: Time Weight Average STEL: Short Time Exposure Limit PEL: Permissible exposure limit **REL: Recommended exposure limit** TLV: Threshold Limit Values + Sensitizer Skin designation Hazard Designation C: Carcinogen M: Mutagen R: Toxic to reproduction **Revision Date:** 2018-12-18

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

*** Indicates updated section.

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained



KIA ORIGINAL OIL 5W-30 A5/B5

Revision Date: 2018-12-18

Version 1

herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet